




MGS48 is a system that is smart, modular and very easy to install. Its magnetic system allows for great flexibility with the lighting design of each space and lets us decide at the last moment which models we are going to use, since we can install the luminaires without the need for screws or any kind of tool. And, on top of that, the end user has the possibility to change the lighting design of his room depending on the needs of each moment. These qualities make the MGS48 system one of the most adaptable to current needs, plus we should always keep in mind that it also adjusts well to different kind of budgets



Suspended, Surface & Recessed





RIERA ORDEIX SHOP / PROJECT: SANDRA SOLER STUDIO / PHOTO: MONTSE CAPDEVILA




RIERA ORDEIX SHOP / PROJECT: SANDRA SOLER STUDIO / PHOTO: MONTSE CAPDEVILA





PROJECT: SANDRA SOLER STUDIO





1. Profile

Reference	Description	Finish	
58.UM2M	Track 2m Short Surface / Suspended	10 White 20 Black	
 			

2. Accessories

Reference	Description	Finish	Detail
58.UMLCON	L Connector for ceiling	10 White 20 Black	 
58.UMF30 58.UMF30DAL 58.UMF60 58.UMF60DAL	Power Inlet Connector with Cable 30cm ON-OFF Power Inlet Connector with Cable 30cm DALI Power Inlet Connector with Cable 180cm ON-OFF Power Inlet Connector with Cable 180cm DALI	10 White 20 Black	 
58.UMI	I Connector	10 White 20 Black	 
58.UMFA	Flexible Connector	10 White 20 Black	 
58.UMGNW	End Cover	10 White 20 Black	 




Reference	Description	Finish	Detail
58.UMGW	End Cover with side hole for wire	10 White 20 Black	 
58.UMLCOU	Coupler 180° between track-track or corner-track	10 White 20 Black	 
58.UMD	Pendant Kit	10 White 20 Black	 
58.UMA 58.UMB	L Corner 90° Horizontal - mechanical L Corner 90° Vertical - mechanical	10 White 20 Black	 




1. Profile

Reference	Description	Finish
58.UMA2M	Track 2m High Surface / Suspended	○ 10 White ● 20 Black

2. Accessories


Reference	Description	Finish	Detail	
58.UMF30 58.UMF30DAL 58.UMF60 58.UMF60DAL	Power Inlet Connector with Cable 30cm ON-OFF Power Inlet Connector with Cable 30cm DALI Power Inlet Connector with Cable 180cm ON-OFF Power Inlet Connector with Cable 180cm DALI	○ 10 White ● 20 Black		
58.UMI	I Connector	○ 10 White ● 20 Black		
58.UMFA	Flexible Connector	○ 10 White ● 20 Black		
58.UMABGNW	End Cover	○ 10 White ● 20 Black		
58.UMABGW	End Cover with side hole for wire	○ 10 White ● 20 Black		




Reference	Description	Finish	Detail
58.UMABD	Pendant Kit	10 White 20 Black	 
58.UMBA	L Corner 90° Horizontal - mechanical	10 White 20 Black	 
58.UMABL	Coupler 180° between track-track or corner-track	10 White 20 Black	 
58.UMABM	Dust-Proof Cover 1.00 M	10 White 20 Black	 

1. Profile




Reference	Description	Finish
58UMBM2	Track Recessed 2.00 M	10 White 20 Black



2. Accessories





Reference	Description	Finish	Detail
58.UMF30 58.UMF30DAL 58.UMF60 58.UMF60DAL	Power Inlet Connector with Cable 30cm ON-OFF Power Inlet Connector with Cable 30cm DALI Power Inlet Connector with Cable 180cm ON-OFF Power Inlet Connector with Cable 180cm DALI	10 White 20 Black	 
58.UMI	I Connector	10 White 20 Black	 
58.UMFA	Flexible Connector	10 White 20 Black	 
58.UMABGNW	End Cover	10 White 20 Black	 
58.UMABGW	End Cover with side hole for wire	10 White 20 Black	 



Reference	Description	Finish	Detail
58.UMABD	Pendant Kit	10 White 20 Black	 
58.UMBA	L Corner 90° Horizontal - mechanical	10 White 20 Black	 
58.UMABL	Coupler 180° between track-track or corner-track	10 White 20 Black	 
58.UMABM	Dust-Proof Cover 1.00 M	10 White 20 Black	 

58110.*.*.*.NDI/DAL

3. Light Modules

NANO PUNCTO	Number	Description	W	CCT	Beam angle	Finish	Dim
 	58110	Spotlight S 480 lm	6	27 2700K	1 15°	○ 10 White	NDI
				30 3000K	2 24°	● 20 Black	DAL
					3 36°		
MICRO PUNCTO	Number	Description	W	CCT	Beam angle	Finish	Dim
 	58110	Spotlight M 1010 lm	12	27 2700K	1 15°	○ 10 White	NDI
				30 3000K	2 24°	● 20 Black	DAL
					3 36°		
PUNCTO	Number	Description	W	CCT	Beam angle	Finish	Dim
 	58110	Spotlight L 2400 lm	30	30 3000K	1 15°	○ 10 White	NDI
					2 24°	● 20 Black	DAL
					3 36°		





PROJECT: SANDRA SOLER STUDIO



PROJECT: SANDRA SOLER STUDIO


3. Light Modules

PANOPTES




Number	Description	W	CCT	Beam angle	Finish	Dim
58120	Linearlight S 236 mm 400 lm	8	27 2700K	2 24°	○ 10 White	NDI
				3 45°	● 20 Black	DAL
58120	Linearlight M 464 mm 1040 lm	16	30 3000K	2 24°	○ 10 White	NDI
				3 45°	● 20 Black	DAL

CONTINUUM



Number	Description	W	CCT	Beam angle	Finish	Dim
58120	Linear Opal S 236 mm 350 lm	8	27 2700K	4 100°	○ 10 White	NDI
					● 20 Black	DAL
58120	Linear Opal S 464 mm 850 lm	16	30 3000K	4 100°	○ 10 White	NDI
					● 20 Black	DAL

POLYPHEMUS








Number	Description	W	CCT	Beam angle	Finish	Dim
58130	Pendant Light 800 lm	10	30 3000K	1 15°	○ 10 White	NDI
				2 25°	● 20 Black	DAL
				3 35°		











PROJECT: SANDRA SOLER STUDIO





4. Accessories Summary

Detail	Reference	Description	Short	High	Rec	Finish	
	58.UMF30	Power Inlet Connector with Cable 30cm ON-OFF	x	x	x	○ 10 White ● 20 Black	
	58.UMF30DAL	Power Inlet Connector with Cable 30cm DALI	x	x	x		
	58.UMF60	Power Inlet Connector with Cable 180cm ON-OFF	x	x	x		
	58.UMF60DAL	Power Inlet Connector with Cable 180cm DALI	x	x	x		
	58.UMI	I Connector	x	x	x	○ 10 White ● 20 Black	
	58.UMFA	Flexible Connector	x	x	x	○ 10 White ● 20 Black	
	58.UMLCON	L Connector for ceiling	x	-	-	○ 10 White ● 20 Black	
	58.UMA	L Corner 90° Horizontal - mechanical	x	-	-	○ 10 White ● 20 Black	
	58.UMB	L Corner 90° Vertical - mechanical	x	-	-	○ 10 White ● 20 Black	
	58.UMAA	L Corner 90° Horizontal - mechanical	-	x	-	○ 10 White ● 20 Black	
	58.UMBA	L Corner 90° Horizontal - mechanical	-	-	x	○ 10 White ● 20 Black	

Detail	Reference	Description	Short	High	Rec	Finish	
	58.UMD	Pendant Kit	x	-	-	○ 10 White ● 20 Black	
	58.UMABD	Pendant Kit	-	x	x	○ 10 White ● 20 Black	
	58.UMLCOU	Coupler 180° between track-track or corner-track	x	-	-	○ 10 White ● 20 Black	
	58.UMABL	Coupler 180° between track-track or corner-track	-	x	x	○ 10 White ● 20 Black	
	58.UMGNW	End Cover	x	-	-	○ 10 White ● 20 Black	
	58.UMGW	End Cover with side hole for wire	x	-	-	○ 10 White ● 20 Black	
	58.UMABGNW	End Cover	-	x	x	○ 10 White ● 20 Black	
	58.UMABGW	End Cover with side hole for wire	-	x	x	○ 10 White ● 20 Black	
	58.UMABM	Dust-Proof Cover 1.00 M	-	x	x	○ 10 White ● 20 Black	


5. Drivers

Reference	Description	W
D4875	Driver 48VDC 75W VSLH 186691	75W
		
D48120	Driver 48VDC 120W VSLH 186692	120W
		




6. Examples

Profile 58.UM2M Short Suspended



Profile 58.UMA2M High Suspended



Profile 58.UM2M2 Recessed

